

## Oxylog® 3000 plus

Offering high ventilation performance with features such as AutoFlow, integrated capnography and non-invasive Ventilation, the compact and robust Oxylog® 3000 plus helps you transport your patients safely and provides feedback on correctness of intubation and ventilation effectiveness. The Oxylog® 3000 plus gives you confidence to master even the most demanding situations.



### TECHNICAL DATA

The Oxylog 3000 plus is a time-cycled, volume-controlled and pressure-controlled emergency and transport ventilator for patients requiring mandatory or assisted ventilation with a tidal volume from 50 mL upwards.

Dimensions (W x H x D)	290 x 184 x 175 mm (without handle and protection bracket)
Weight	Approximately 5.8 kg (including internal battery)
<b>Gas supply</b>	
Supply gas	Medical Oxygen
Gas supply	From a pipeline system or from an O <sub>2</sub> cylinder.
O <sub>2</sub> service pressure	270 kPa to 600 kPa at 100 L/min
Gas consumption for internal control	Average 0.5 L/min
<b>Operating data</b>	
Ventilation Modes	VC-CMV, VC-AC, VC-SIMV, SpnCPAP, PC-BIPAP
Additional settings for ventilation	<ul style="list-style-type: none"> <li>- Pressure support: in the ventilation modes VCSIMV, PC-BIPAP* and SpnCPAP</li> <li>- Apnoea ventilation: in the ventilation mode SpnCPAP</li> <li>- AutoFlow (optional): in the ventilation modes VC-CMV, VC-AC and VC-SIMV</li> <li>- NIV: in the ventilation modes: SpnCPAP (/PS), PC-BIPAP (/PS), VC-CMV /AF, VC-AC /AF and VC-SIMV /AF</li> </ul>
Special procedures	<ul style="list-style-type: none"> <li>- Inspiration hold</li> <li>- O<sub>2</sub> inhalation (optional), with an inhalation mask</li> <li>- 100% O<sub>2</sub></li> </ul>
Options	<ul style="list-style-type: none"> <li>- Integrated mainstream CO<sub>2</sub> measurement (**)</li> <li>- Real time data export via RS232, MEDIBUS protocol (**)</li> <li>- AutoFlow: volume targeted - pressure controlled ventilation (**)</li> </ul>
CPR-behavior	Pressure-limited, non-constant-volume ventilation during inspiration time when Pmax is reached
Ventilation Respiratory Rate	2 to 60 /min (VC-SIMV, PC-BIPAP) 5 to 60 /min (VC-CMV, VC-AC) 12 to 60 /min for apnoea ventilation
Tidal volume VT	0.05 to 2.0 L; BTPS***
Ti / I:E	I:E or Ti configurable, for all ventilation modes
Ventilation time ratio I:E	1:100 to 50:1



D-9219-2009

Oxylog® 3000 plus

Inspiration time $T_i$	0.2 to 10 s	Apnea back-up ventilation	When respiratory activity is no longer detected, adjustable time from 15 to 60 s
Inspiratory pressure $P_{insp}$	PEEP +3 to +55 mbar	Leakage	$VT_e$ is approx. 40% lower than $VT_i$ (not applicable in NIV)
O <sub>2</sub> concentration	40 to 100 Vol.% (****)	High Respiratory Rate	Patient breathes at a high spontaneous rate
PEEP / CPAP	0 to 20 mbar	etCO <sub>2</sub> high / low	When the alarm limits for end-expiratory CO <sub>2</sub> concentration have been exceeded.
Trigger sensitivity (flow trigger)	1 to 15 L/min	MVe high/ low	When the alarm limits for expiratory minute volume have been exceeded.
Pressure support $\Delta P_{supp}$	0 to 35 mbar (relative to PEEP)	Incorrect patient hose	Ventilator detects if incorrect patient hose type is connected
Slope (pressure rise time)	Slow, standard, fast	Supply pressure low	Supply pressure < 270 kPa
Max. inspiratory flow	100 L/min @ supply pressures > 350 kPa / 51 PSI; 80 L/min @ supply pressures < 350 kPa / 51 PSI; 39 L/min @ supply pressures < 270 kPa / 39 PSI	<b>Operating Conditions</b>	
Displayed measured values	MVe, FiO <sub>2</sub> , RR, VT <sub>e</sub> , PEEP, P <sub>mean</sub> , PIP, P <sub>plat</sub> , MV <sub>esp</sub> , RR <sub>spon</sub> , etCO <sub>2</sub> .	Temperature range	-20 to +50 °C for basic device
Display type	Technology Electro-luminescence (EL) Pixels 240 x 128 Visible area 108 x 56 mm	Temperature range for CO <sub>2</sub> sensor	+10 to +40 °C
Curve display	Airway pressure Paw curve, flow curve, CO <sub>2</sub> curve (optional)	Atmospheric pressure	570 to 1200 hPa for basic device
Patient hose types	Reusable adult hose (1,5m / 3m), Disposable adult hose (1,5m / 3m), Disposable pediatric hose (1,9m)	Relative humidity	5 to 95 % (no condensation)
<b>Power supply</b>		Electromagnetic compatibility (EMC)	In accordance with IEC/EN 60601-1-2:2007, EN 794-3 and ISO 10651-3
Oxylog 3000 plus input voltage	24 V ±6 VDC	Airworthiness	In accordance with RTCA DO-160F, sections 7, 8, 16.6, 18.3.1, 17, 19.31, 20, 21, 25
Input voltage AC/DC power pack	100 to 240 V~ / 50 to 60 Hz / 0.9 to 0.4 A~	Mechanical strength	In accordance with MIL STD 810F, method 514.5
Input voltage DC/DC converter	12 / 24 / 28 VDC; 5 A / 2.5 A / 2.1 A	Classification according to MDD 93/42/EEC	Class IIb
Battery type	Lithium ion battery	UMDNS-Code	18-098
Operating time (fully charged, "typical" ventilation)	Approximately 4 hours	* Trademark used under License	
Battery charging time	Approximately 5 hours	** Options can be purchased during the initial ordering process or as future upgrades.	
<b>Main alarms</b>		*** BTPS: Body Temperature, Pressure, Saturated. Measured values referred to the conditions of the patient's lungs, body temperature 37 °C / 99 °F, airway pressure, water-vapour-saturated gas.	
Airway pressure (Paw) high	Adjustable from 20 to 60	**** Indirect measurement of O <sub>2</sub> concentration (calculated from two measured flows).	
Airway pressure (Paw) low	When pressure difference between Insp. and Exp. < 5 mbar or when the set pressure level is not reached		

**HEADQUARTERS**

Dräger Medical AG & Co. KG  
Moislinger Allee 53-55  
23558 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

**REGION EUROPE CENTRAL AND EUROPE NORTH**

Dräger Medical AG & Co. KG  
Moislinger Allee 53-55  
23558 Lübeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
info@draeger.com

**REGION EUROPE SOUTH**

Dräger Médical S.A.S.  
Parc de Haute  
Technologie d'Antony 2  
25, rue Georges Besse  
92182 Antony Cedex  
Tel +33 1 46 11 56 00  
Fax +33 1 40 96 97 20  
dlmfr-contact@draeger.com

**REGION MIDDLE EAST, AFRICA, CENTRAL AND SOUTH AMERICA**

Dräger Medical AG & Co. KG  
Dubai Healthcare City  
P.O. Box 505108  
Dubai, United Arab Emirates  
Tel +971 436 24 762  
Fax +971 436 24 761

**REGION ASIA / PACIFIC**

Draeger Medical  
South East Asia Pte Ltd  
25 International Business Park  
#04-27/29 German Centre  
Singapore 609916  
Tel +65 6572 4388  
Fax +65 6572 4399  
asia.pacific@draeger.com

**Manufacturer:**

Dräger Medical b.v.  
NL-5683 CR Best  
The quality management system at Dräger Medical b.v. is certified according to ISO 13485, ISO 9001 and Annex II.3 of Directive 93/42/EEC (Medical devices).